




9

- 9-2
- 9-3
- 9-4


- 9-5
- 9-6

(VIN)

VIN




()	1.5B DOHC	3,75	Dexos1 5W20
		7,2	DEX-COOL
		4,5 - 5,0 (±0,5)	DEXRON 6
		1,8	SAE 75W-90
/		0,5	DOT 3
		1,1	DEXRON 2D





API

(ILSAC)

(API).
API SL (ILSAC GF-III)



			x	
	1		60/55 x 2	
	2		5 x 2	
	3		21 x 2	
	4	*	21 x 2	
	5	1)	35 ?? x 2	
	6	*	5 x 2	
	7		21 x 2	
	8	- /	21/5 x 4	
	9		21 x 2	
	10	*	21 x 2	
	11	- *	5 x 5	
	12		5 x 2	
			10 x 1	
			7,5 x 2	
			10 x 1	



(1.5 DOHC)		
	4-	/
	DOHC 16	
(.)	1485	
()	74,7 x 84,7	
	10,2 : 1	
AX (/ . .) II	77,5 / 5800	
AX (/ . .) V	79 / 5800	
(/ . .)	141 / 3800	
	RON 91	
	()	0,8 ~ 0,9
	(- -)	12 - 55
	- (CCA)	610
(-)	12 - 100	
(-)	12 - 1,2	

()			-0° 20' ± 45'
			-1° 00' ± 45'
			4° 00' ± 45'
			0° 00' ± 10'
			0° 12' ± 10'
			,
	/		16:1
	Ø ()		380 () 370 ()
	()		5,2

	() []	9,5" [241,3]
	() []	7"+8" [177,8+203,2]

(.)	60
()	(3.75)
(.)	7.2

()	
()	4 515
()	1 725
()	1 445
()	2 600
()	1 480
	1 480

(/)	1.5 DOHC		180
			171

()			
		() [psi]	
		3-	
185/65 R14	5,5J x 14	210 [30]	210 [30]
195/55 R15	6J x 15	210 [30]	210 [30]

6- (1.5 DOHC)		
	1-	4,449
	2-	2,908
	3-	1,893
	4-	1,446
	5-	1,000
	6-	0,742
		-2,871
		4,110

	,
()	215
()	145
()	8,3

5- (1.5 DOHC)		
	1-	3,727
	2-	1,952
	3-	1,276
	4-	0,971
	5-	0,763
		3,545
		4,467

(1.5 DOHC)		
()		1170~1225
		1190~1245
()		1660
		1680
()		920
()		845